



COMMANDER NEO

HIGH-SPEED MIL-GRADED SATELLITE ANTENNA FOR ON-THE-MOVE

On-the-move connectivity redefined: delivers seamless, high-speed voice and data communication from vehicles, trains, or any mobile platform, no matter the mission.

Always mission-ready: compact, rugged, and built without moving parts, ensuring maximum durability and reliability even in the harshest conditions.

Instant mobile hub: transforms any vehicle into a secure communications center in minutes, keeping teams connected wherever operations take them.



COMMANDER NEO

Specifications

Dimensions:

Height: 11.7 cm (with 3 cm spacers)
Width: Ø 32.1 cm

Weight: 4.8 kg

Data Capabilities

> 5° elevation: Up to 1024 kbps (Rx / Tx)

Voice

Standard VoIP
Embedded SIP Server
PPT Push-To-Talk with Mobile
Neo M

Frequency Range:

Tx (MHz) 1626.5 - 1660.5 and 1668 - 1675
Rx (MHz) 1518.0 - 1559.0

Frequency Range: GPS, Galileo, Beidou, Glonass

Languages: EN, AR, FR, DE, ES, RU, JP, CN

Approval: CE, RED, RoHS, WEEE,
FCC, UL, RCM
Thuraya Type Approval

Environmental conditions

Temperature

Operational: -25°C to +55°C (ambient)
Storage: -40°C to +85°C

Water and dust: IP68

MIL-STD-810G: Method 503.6 (Temperature shock)
Method 505.6 (Solar Radiation)
Method 506.6 (Rain)
Method 507.6 (Humidity)
Method 509.6 (Salt Fog)
Method 510.6 (Sand and Dust)
Method 512.6 (Immersion)
Method 516.7 (Drop)
Method 524.1 (Freeze/Thaw)

EMI/EMC: MIL-STD-461H

Power

DC input range: 12 - 24 VDC (Max. 10.8 to 32 VDC)

Power (max): 70W (@10.5 - 32V)

Interfaces

WLAN Access Point: 802.11 b/g/n/ac

Ethernet: 10 / 100 / 1000 Mbps

Combined DC power and Ethernet connector:

Combined connector providing DC power input, ignition and Ethernet (PoE 802.3bt Type 3) connectivity.

User interface:

One LED (Status), Web Interface,
Reset Button, SIM card connector

Other features

Space42 Connect App:

Turns a Smartphone into a Satphone.
Available for Android / IOS.

Set-up and Router Functionality:

Webserver, NAT Router, Admin control
(password protected), DHCP, Network Management,
Remote Management, PPPoE

Package

- Commander NEO Terminal with 3cm spacers
- Quick Start Guide
- 6m hybrid DC power and Ethernet cable (open-ended)

Accessories

- Connection Box for NEO
- PoE Cable Connection cable (Cat5e), 6m
- PoE Cable Connection cable (Cat5e), 15m open-ended
- PoE Cable Connection cable (Cat5e), 25m open-ended
- PoE Cable Connection cable (Cat5e), 50m open-ended
- Hybrid DC/ethernet connection cable (6m open-ended)
- Hybrid DC/ethernet connection cable (25m open-ended)
- Magnetic Mount Kit

