

IP HANDSET

- Superior voice clarity with advanced VoIP audio technology, ensuring every conversation is clear, reducing misunderstandings and improving communication efficiency.
- Stable and uninterrupted communication with direct Ethernet connectivity, ensuring consistent voice quality and minimizing the risk of dropped calls.
- Durable **coiled cable** with watertight screw connector offers flexibility and convenience, preventing tangles while allowing the handset to stretch to a comfortable reach.
- Easy **integration** with Thuraya PTT and Space42 NEO terminals. Plug-and-play with minimal configuration.

Specifications

Dimensions (LxWxD):	178.5 x 70 x 30 mm
Weight:	250 g (without cable)
Certifications:	CE, FCC, IC, RCM, Anatel

Power

PoE:	PoE I	PD (8	02.a) Type	1 (mode	A 8	k B)
Power Consumpti	on:	Max.	7 W	att				

Environmental conditions

remperature	
Operational: Storage:	-25° to +55° -40° to +80°
_	

Humidity: Up to %95 (w/o condensation)

Air Pressure (transport): At low pressure 18.8 kPa (12.192 m = 40.000 ft)

MIL-STD-810H:

Method 503.7 (Temp. shock)
Method 507.6 (Humidity)
Method 512.6 (Immersion)
Method 524.1 (Freeze/Thaw)
Method 505.7 (Solar Radiation)

IP Rating: IP66 and IP68 (IEC60529)

Protocols

Network Protocol:	Internet Protocol (IP)
VoIP Protocol:	SIP v2 Session Initiation Protocol (RFC3261), SDP
Voice Codecs:	G711 and G729

Interfaces

LAN Interface:	10/100 Mbps
Physical Interface:	RJ-45 male connector on coiled cable (3 m)

Keypad and buttons

Keypad:	Numeric keypad for dialing
5 Control Keys:	Left / right select, Off Hook, On Hook / Power, Select
Navigational Arrows:	Right, Left, Up (Volume +), Down (Volume -)
Distress Button:	Configurable on the back
Side Buttons:	Stealth, Lock, PTT

Product number

408012A-41000 Space42 IP Handset

Related products

408050A-42000 Mobile Gateway C NEO 408052A-42000 Mobile Gateway M NEO 408020A-40000 IP NEO C Terminal 408022A-41000 IP NEO M Terminal

